




# 350 'C` Section Steel Joists

**Copyright © Supercrete Limited 2008**

Without limiting the rights of the copyright above, no part of this publication shall be reproduced (whether in the same or a different dimension), stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording or otherwise), without the prior permission of the copyright owner.




### Construction R Values for Supercrete™ 75mm Soundfloor with 350 "C" Section Steel Joists

Joist Depth	Insulation			
	R 1.3 Board	R 1.3 Blanket	R 2.0 Blanket	R 2.6 Blanket
360mm	2.06	1.56	1.91	2.17
450mm	2.055	1.6	2.01	2.31
600mm	2.05	1.64	2.11	2.46
Solid 1a, 2a & 3a	1.5	1.5	1.5	1.5
All non-solid; 1b, 2b & 3b solid	1.3	1.3	1.3	1.3

1. For open/exposed sub-floors. Add the R Values for ground under a suspended floor (see separate sheet) to the above figures.
2. Add floor covering R Values to the above figures.

### Construction R Values for Supercrete™ 75mm Soundfloor with 350 "C" Section Steel Joists



1. For open/exposed sub-floors. Add the R Values for ground under a suspended floor (see separate sheet) to the above figures

2. Add floor covering R Values to the above figures
3. Line R 1.5 is NZBC minimum required for Solid Construction (excluding solid timber) for Zones 1a, 2a & 3a
4. Line R 1.3 is NZBC minimum required for Non-solid Construction for all Zones & Zones 1b, 2b & 3b for Solid Construction (excluding solid timber)